Attorney Docket: 5171-140

EV141146435OUS

APPLICATION

FOR

UNITED STATES LETTERS PATENT

TITLE: HEIGHT-ADJUSTMENT MECHANISM FOR AN ARMREST

APPLICANT: Gerard J. Matern
David Lloyd Hobb
Gerard Helmond
Arthur A. Patton
Cuong Quoc Vo
David Watkins

HEIGHT-ADJUSTMENT MECHANISM FOR AN ARMREST

BACKGROUND OF THE INVENTION

[0001] The present invention relates generally to adjustable chairs, and more particularly to a height-adjustment mechanism for an armrest.

[0002] Various designs for height-adjustable armrests are known. Some known designs require numerous parts and relatively expensive materials, making such designs less cost competitive. Other known designs include relatively few parts, making them generally less expensive, but such designs may not appear to be of a high quality.

[0003] For example, U.S. Patent No. 5,318,347 issued to Tseng ("Tseng '347") discloses a design for a height-adjustable armrest unit comprising an L-shaped support bar, a vertical sleeve, and a leverage body. In Tseng '347, a tongue provided at a lower end of the leverage body is adapted to engage a positioning hole located on the support bar. The leverage body may be pivoted to disengage the tongue from the positioning hole to allow the sleeve (and the leverage body) to be vertically adjusted relative to the support bar. While Tseng '347 may reduce product cost with fewer parts, the design may not provide a user with a sense that the armrest adjustment mechanism is of a high quality.

[0004] Consequently, what is needed is a height-adjustment mechanism for an armrest which can be manufactured at a low cost, yet is long-lasting and capable of giving a user a sense of high quality.

SUMMARY OF THE INVENTION

[0005] The present invention provides a height-adjustment mechanism for an armrest. In an embodiment, the height-adjustment mechanism includes an integral one-piece leverage body; an integral one-piece sleeve; and a locking member. These parts may be made of low cost materials suitable for integrally forming their features in an injection-

moulding operation. Various features built into these parts may provide a user with a sense of quality.

[0006] In an embodiment, the integral one-piece leverage body has a handle, a pair of pivot pins projecting from opposed sides, a tongue projecting rearwardly, and a resilient biasing member projecting forwardly.

[0007] The leverage body may be elongate, with the handle located at an upper portion of said body, the tongue located at a lower portion of the body, and the pair of pivot pins located intermediately between the handle and the tongue.

[0008] The leverage body may be made of a material suitable for integrally forming the handle, the pivot pins, the tongue and the resilient biasing member in an injection-moulding operation.

[0009] The height-adjustment mechanism may further comprise an integral, one-piece sleeve having pivot seats receiving the pivot pins of the leverage body.

[0010] The sleeve may be made of a material suitable for forming the pivot seats and the ribs in an injection-moulding operation.

[0011] The height-adjustment mechanism may further comprise a support, and a plurality of ribs extending from inner walls of the sleeve to form a channel slidably receiving the support.

[0012] The height-adjustment mechanism may further comprise a locking member locking the pivot pins of the leverage body in the pivot seats.

[0013] The locking member may be formed of a material suitable for forming the locking member in an injection-moulding operation.

[0014] Anti-rattling fingers may be provided to prevent rattling between the various parts of the height-adjustment mechanism.

[0015] These and other aspects of the invention will become apparent through the illustrative figures and accompanying description provided below.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] In the figures which illustrate example embodiments of this invention:

FIG. 1 is a view of an illustrative chair that may embody the invention.

FIG. 2 is an exploded perspective view of a height-adjustment mechanism for an armrest in accordance with an embodiment of the invention.

FIG. 3 is a cross sectional side view of the height-adjustment mechanism of **FIG. 2** showing the leverage body in a first position.

FIG. 4 is the cross sectional side view of **FIG. 3** showing the leverage body in a second position.

FIG. 5A is a cross sectional side view of a portion of the height-adjustment mechanism of **FIG. 2**.

FIG. 5B is a cross sectional view of another embodiment of this invention.

FIG. 6 is a cross sectional front view of a portion of the height-adjustment mechanism of **FIG. 2** showing a feature detail of yet another embodiment of the invention.

FIGS. 7A – 7E are views of a feature detail of yet another embodiment of the invention.

FIG. 8 is a perspective view of another embodiment of the leverage body of **FIG. 2**.

DETAILED DESCRIPTION

[0017] Referring to **FIG. 1**, shown is an illustrative chair **11** that may embody the present invention. The chair **11** has a chair seat **13** mounted on a chair seat frame **10** and supported by a chair seat support **21**. A backrest **15** is supported on a backrest support **17**, and the backrest support **17** is mounted on the chair seat frame **10**. The chair **11** may further include a pair of armrests, each armrest including a height-adjustment mechanism **20** supported on an armrest support **30**.

[0018] **FIG. 2** shows an exploded perspective view of a height-adjustment mechanism **20** in accordance with an exemplary embodiment of the invention. As shown, the height-adjustment mechanism **20** may include a sleeve **40**, a leverage body **60**, and a locking member **70**. The sleeve **40**, with leverage body **60**, are adapted to mount to, and engage, the armrest support **30**, as explained below.

[0019] In the exemplary embodiment, the support **30** is an L-shaped bar having a first arm **30a** and a second arm **30b**. In use, the first arm **30a** is generally horizontally oriented and may include a plurality of mounting holes **32** for mounting the support **30** to the chair seat frame **10** (using mounting screws, not shown). The generally vertically oriented second arm **30b** of the support **30** may include a plurality of vertically spaced slots **34**. In an embodiment, a vertical groove **36** may join all of the slots **34**. As will be explained further below, a protruding tongue **64** formed on a lower portion of the leverage body **60** is adapted to selectively engage one of the slots **34**, and the vertical position of the slot **34** engaged by the tongue **64** will determine the vertical position of the height-adjustment mechanism **20**.

[0020] In order to support the height-adjustment mechanism **20**, and the weight placed on the height-adjustment mechanism **20** by an occupant of the chair **11**, the support **30** should be made of a sufficiently strong and rigid material. For example, in the exemplary embodiment, an elongate plate made of steel, or another suitable metal, may be used. Other materials such as reinforced plastics and carbon composites may also be used.

[0021] Still referring to **FIG. 2**, the sleeve **40** may be formed as an integral, single-piece, injection-moulded structure. For example, the sleeve **40** may be formed of a plastic material that may be injection-moulded in the desired shape. As shown, the sleeve **40** is adapted to be vertically oriented in use and has an upper end **42** and a lower end **43**. The lower end **43** of the sleeve **40** has an opening **44** suitably sized to receive the generally vertically oriented second arm **30b** of the armrest support **30**. The upper end **42** of the sleeve **40** is suitably shaped to receive an armrest pad **50** (**FIG. 3**). Mounting holes **41a** and **41b** are provided at the upper end **42** of the sleeve **40** to mount the armrest pad **50** (using mounting screws, not shown).

[0022] Still referring to **FIG. 2**, the sleeve **40** is shown in a partial cutout view with an arrangement of structural reinforcing ribs located on each inside wall of the sleeve **40**. A first pair of reinforcing ribs **48a**, **48b** is located on a first inside wall **48** of the sleeve **40**. A second pair of reinforcing ribs **52a**, **52b** is provided on an opposite inside wall **52** of the sleeve **40**. Additional reinforcing ribs **54a** and **56a** are provided on inner side walls **54** and **56**, respectively, which extend between the first and second walls **48** and **52**.

[0023] Together, the edges of the reinforcing ribs **48a**, **48b**, **52a**, **52b**, **54a** and **56a** form a "channel" **45**. As shown, the channel **45** is aligned with opening **44** to slidably receive the vertically oriented second arm **30b** of the support **30**.

[0024] Still referring to **FIG. 2**, a notch **58** is provided at the top of the first wall **48** of the sleeve **40**. As shown, the notch **58** is substantially centered between the reinforcing ribs **48a** and **48b** and suitably sized to allow a portion of the leverage body **60**, namely the handle **68**, to extend outside the sleeve **40**. A pair of pivot seats **53a** and **53b** are provided at the top of the reinforcing ribs **48a** and **48b** to position the handle of the leverage body **60** through the notch **58**. The leverage body **60** is then free to pivot about the pivot seats **53a**, **53b** when the handle **68** is moved by an operator.

[0025] In the exemplary embodiment, a pair of mounting posts **59a** and **59b** is integrally formed on the sleeve **40** and are located adjacent the pivot seats **53a**, **53b**. These mounting posts **59a**, **59b** may be used to lock the leverage body **60** in position, using a locking member **70**, as described further below.

[0026] Still referring to **FIG. 2**, the leverage body **60** is formed as an integral, single-piece, injection-moulded body. For example, the leverage body **60** may be made of a plastic material injection-moulded into the desired shape. In the exemplary embodiment, the leverage body has a generally elongate body with a pair of pivot pins **62a**, **62b** located intermediately along its length. The tongue **64**, as mentioned earlier, protrudes from a lower portion of the elongate leverage body **60**. Also, a biasing member **66** is integrally formed with the leverage body **60** and extends outwardly in a direction opposite the tongue **64**. As mentioned, a handle **68** is provided at an upper end of the leverage body **60**. The handle **68** allows an operator to pivot the leverage body **60** about the pivot pins **62a**, **62b**. In

operation, the biasing member **66** provides a biasing force, acting against the force applied by the operator to the handle **68** of the leverage body **60**.

[0027] With the integral, one-piece, injection-moulded leverage body **60**, advantageously, the most wearable parts -- the protruding tongue **64**, the pivot pins **62a**, **62b**, and the biasing member **66** -- are all provided on one smaller part which, at the end of its life, may be readily replaced at relatively little cost.

[0028] Still referring to **FIG. 2**, the locking member **70** is preferably formed as an integral, single-piece, injection-moulded body. For example, the locking member **70** may be made of a plastic material that may be injection-moulded into the desired shape. In the exemplary embodiment, the locking member **70** has a frame **72** having first and second arms **72a**, **72b**. At the end of each arm **72a**, **72b**, first and second pivot caps **73a**, **73b** are formed to engage the top of pivot pins **62a**, **62b**, when these pivot pins **62a**, **62b** are seated in the pivot seats **59a**, **59b**. The locking member **70** may further include first and second laterally extending wings **76a**, **76b** provided with mounting holes **78a** and **78b**, respectively. As shown in **FIG. 3**, these mounting holes **78a** and **78b** may be received by mounting posts **59a** and **59b** formed on the sleeve **40** to mount the locking member **70** to the sleeve **40**. If the leverage body **60** is placed such that pivot pins **62c**, **62b** are received by pivot seats **53a**, **53b**, and the locking member **70** is mounted, locking member **70** locks the pivot pins **62a** and **62b** in place, while still allowing the leverage body **60** to pivot.

[0029] In an embodiment, the locking member **70** may be suitably sized and shaped such that, once mounted, the top of its frame **72** is substantially flush with the top **42** of the sleeve **40**. Thus, when an armrest pad **50** is secured to the top of the sleeve **40** (for example by mounting screws mounted through mounting holes **41a** and **41b**), the locking member **70** may be held securely in position on the mounting posts **59a** and **59b**. The laterally extending wings **76a**, **76b** of the locking member **70** may be suitably sized and shaped such that these laterally extending wings **76a**, **76b** engage one or more of the reinforcing ribs within the sleeve **40**. This may further reinforce the locking member **70** laterally, such that the leverage body **60** is held securely in position.

[0030] In another embodiment, once the locking member **70** has been mounted in position on the mounting posts **59a**, **59b**, the tip of the mounting posts may be deformed, for example by the application of heat, such that the locking member **70** is locked on the mounting posts **59a**, **59b**. This is advantageous where the height-adjustment mechanism **20** may be shipped as a unit prior to its incorporation in a chair. In other circumstances, as the locking member **70** may be kept securely in position by mounting the armrest pad **50**, and by lateral reinforcement of the reinforcing ribs, the mounting posts **59a**, **59b** may be left as is such that the leverage body **60** may be readily replaced, if necessary.

[0031] The height adjustment operation of the height-adjustment mechanism **20** will now be explained.

[0032] Referring to **FIG. 3**, the sleeve **40** is shown mounted on the vertically oriented second arm **30b** of the armrest support **30**. The leverage body **60** is shown with its pivot pins **62a** and **62b** seated within the pivot seats **53a** and **53b** and secured thereat by the locking member **70**.

[0033] As shown in **FIG. 3**, the handle **68** of the leverage body **60** extends through the notch **58** in the first wall **48** of sleeve **40**. Within the sleeve **40**, the biasing arm **66** of leverage body **60** engages the first wall **48** and biases the leverage body **60** away from the first wall **48**. When the leverage body **60** is not actuated by an operator, the biasing force provided by the biasing arm **66** causes the tongue **64** protruding from the lower arm of the leverage body **60** to continuously engage one of the slots **34** in the support **30**. As noted earlier, the vertical position of the slot **34** engaged by the tongue **64** determines the vertical height of the height-adjustment mechanism **20**.

[0034] As shown in **FIG. 4**, in order to adjust the height of the height-adjustment mechanism **20**, the handle **68** of leverage body **60** may be lifted or pulled back by an operator in direction **A**. This action by the operator will cause the leverage body **60** to pivot about pivot pins **62a** and **62b**, against the biasing force of the resiliently flexible biasing arm **66**. The biasing arm **66** is resiliently deformed when the handle **68** is lifted by the operator such that the biasing arm **66** will act to reengage the tongue **64** with one of the slots **34** when the handle **68** is released.

[0035] In one embodiment, the tongue **64** includes a base **64a**, and a tip **64b**. As shown, when the leverage body **60** is pivoted about pivot pins **62a** and **62b**, the base **64a** of the tongue **64** disengages from the slots **34**, as shown at **B**. However, the tip **64b** of the tongue **64** remains engaged in the vertical groove **36** (**FIG. 2**). As the vertical groove **36** runs the length of the slots **34**, the leverage body **60** and the sleeve **40** may be adjusted vertically, as indicated at **C**, relative to the support **30**. The tongue **64** continuously guides the leverage body **60** within the vertical groove **36**, thereby allowing the base **64a** of tongue **64** to more readily engage any one of the slots **34** when the operator finally releases the handle **68**.

[0036] In an embodiment, the vertical adjustment of the height-adjustment mechanism **20** by the operator may be limited at an upper and lower limit by the tip **64b** of the tongue **64** engaging the top and bottom of the slot **36**.

[0037] Referring to **FIG. 5A**, in an embodiment, an offset **38** may be formed in the support **30** at the top of the vertical groove **36** to accommodate and guide the tip **64b** of the tongue **64** of the leverage body **60** when the height-adjustment mechanism **20** is first slidably received on the support **30**. When this offset **38** is provided, a separate feature may be provided to limit vertical adjustment of the height-adjustment mechanism **20**. For example, a protuberance **39** (seen from the back in **FIG. 2**) may be formed and suitably located on the vertically oriented second arm **30b** of the support **30**. The protuberance **39** may be ramped in a downward direction such that an inwardly extending part **45** of sleeve **40** will deform and pass over the protuberance **39** on the way down, when the sleeve **40** is first installed, but the inwardly extending part **45** of sleeve **40** will catch on the protuberance **39** on the way up. Thus, the protuberance **39** may prevent the height-adjustment mechanism **20** from being inadvertently lifted clear off the support **30** by the operator.

[0038] Referring to **FIG. 5B**, as shown in this alternative embodiment, the offset **38** of **FIG. 5A** may be absent. In this case, in order to assist in fitting the tip **64b** of the tongue **64** over the top of the support **30** and into the vertical groove **36** (**FIG. 2**) during assembly, a ramped surface **64c** may be provided on the lower portion of the tip **64b**. As the tip **64b** otherwise remains the same, the tip **64b** having the ramped surface **64c** may continue to engage the vertical groove **36,** as described above.

[0039] Referring to **FIG. 6**, in a further embodiment, a flexibly resilient anti-rattling finger **46** may be formed on one of the inner side walls **54**, **56** of the sleeve **40** to flexibly bias the support **30** against the opposite one of the inner side walls **54**, **56** of the sleeve **40**. In operation, the anti-rattling finger **46** acts to reduce or prevent rattling between the sleeve and the support **30**, providing the operator of the height-adjustment mechanism **20** with a more smooth and solid feel.

[0040] Referring to **FIGS. 7A – 7E**, in a further embodiment, rather than moulding a resilient finger **46** in sleeve **40**, the sleeve **40** may be moulded to include a track **82** along a length of a reinforcing rib **54b'**. As shown in **FIG. 7d**, the track **82** may have retaining walls **83** to retain an insert **84** having a plurality of projecting anti-rattling fingers **86**. The anti-rattling fingers **86** extend to abut an edge of the support **30**. The anti-rattling fingers **86** are resiliently flexible and may be suitably shaped and sized so they will push the support **30** against the opposite side of the channel **45** (**FIG. 2**) of sleeve **40** to remove any tolerances between the sleeve **40** and the support **30**. In this regard, the insert **84** may be made integrally formed of a resilient plastic material. Advantageously, the anti-rattling fingers **86** may provide a smooth gliding action when the height-adjustment mechanism **20** is adjusted. In order to keep the insert **84** from sliding out of the track **82**, a suitable cap may be provided on top of the track **82**. For example, as shown in **FIG. 7e**, an extension **79** may provided on the locking member **70** in order to contain the insert **84** within the track **82**.

[0041] In yet another embodiment, as shown in **FIG. 8**, an alternative leverage body **60'** has a biasing member **66'** extending from a bottom end, rather than extending from an intermediate region (as shown at **60** in **FIG. 2**). It will be apparent that this alternative leverage body **60'** is interchangeable with the leverage body **60** of **FIG. 2**. It will also be apparent that a biasing member may be integrally formed on the leverage body **60** at various other locations, and that such a biasing member may be embodied in various other configurations.

[0042] While an exemplary embodiment of the invention has been shown and described, it will be apparent to those skilled in the art that various modifications and alterations may be made. Therefore, the invention is defined in the following claims.